

# Are Rubflex Friction VC and Square D breakers compatible?

Our company offers different Are Rubflex Friction VC and Square D breakers compatible?, breaker compatibility chart, square d breaker compatibility chart, homeline breaker compatibility chart at Wholesale Price? Here, you can get high quality and high efficient Are Rubflex Friction VC and Square D breakers compatible?

Which Circuit Breakers Are Interchangeable? - RelectricMar 1, 2019 — Manufacturers like Square D warns against the use of Classified and interchangeable breakers. They site the National Electrical Code (NEC)

What breaker is compatible with Square D? Mar 26, 2021 — What breaker is compatible with Square D? The Siemens Type QD circuit breakers have been classified by UL for use in place of the Square D Type Circuit breaker compatibility - Fine HomebuildingJun 6, 2009 — I have a Square D electrical panel, and I want to add in a new 20 amp circuit breaker. Unfortunately, I couldn't seem to find Square D

| Industrial Clutch and Brakes   |                |                                                                                                             |       |               |                                                 |                |                |                 |
|--------------------------------|----------------|-------------------------------------------------------------------------------------------------------------|-------|---------------|-------------------------------------------------|----------------|----------------|-----------------|
|                                | G MM           | H6 MM                                                                                                       | H7 MM | H2 MM         | G1 MM                                           | D2 MM          | D25 MM         | D24 MM          |
| <a href="#">14VC500104611</a>  | -              | -                                                                                                           | -     | -             | -                                               | -              | -              | -               |
| <a href="#">51VC1600104689</a> | Wichita Clutch | 24.88 in; 632 mm                                                                                            | -     | -             | 1.75 in; 44.5 mm                                | 450 hp; 336 kW | -              | -               |
| <a href="#">66VC1600108111</a> | -              | Ed 50/6 for 8500 N Contract Force; Ed 80/6 for 12500 N Contract Force; Ed 80/7bb for 16000 N Contract Force | -     | -             | -                                               | -              | -              | -               |
| <a href="#">46VC1200104727</a> | -              | -                                                                                                           | -     | 19 lb; 8.6 kg | 2.3 lb·ft <sup>2</sup> ; 0.10 kg·m <sup>2</sup> | -              | -              | 4.00 in; 102 mm |
| <a href="#">51VC1600104729</a> | Eaton-Airflex  | 24CB500                                                                                                     | -     | -             | -                                               | -              | -              | -               |
| <a href="#">42VC1200104686</a> | -              | 1.00 in; 25 mm                                                                                              | -     | -             | -                                               | -              | -              | -               |
| <a href="#">42VC650104609</a>  | -              | -                                                                                                           | -     | -             | -                                               | 15 lb; 6.8 kg  | 2.50 in; 64 mm | -               |

|                                      |                       |                            |                                           |                             |                        |                      |                      |                        |
|--------------------------------------|-----------------------|----------------------------|-------------------------------------------|-----------------------------|------------------------|----------------------|----------------------|------------------------|
| <a href="#">46VC120<br/>0 104687</a> | -                     | 15.12 in;<br>384.0 mm      | 380 hp;<br>283 kW                         | -                           | -                      | -                    | 7-325-210<br>-101-0  | -                      |
| <a href="#">32VC100<br/>0 104684</a> | -                     | -                          | -                                         | -                           | -                      | 22CB500              | -                    | 26.500 in;<br>673.1 mm |
| <a href="#">36CB525<br/>406924</a>   | -                     | -                          | -                                         | -                           | -                      | -                    | 5.18 in;<br>132 mm   | -                      |
| <a href="#">30CB525<br/>408343</a>   | AA2                   | -                          | -                                         | 1/8-27                      | AA2                    | -                    | -                    | 1.38 in; 35<br>mm      |
| <a href="#">22CB500<br/>406912</a>   | -                     | -                          | -                                         | -                           | 15.4 in;<br>391 mm     | -                    | -                    | 12.8 in;<br>325 mm     |
| <a href="#">30CB525<br/>40692</a>    | 0.19 in; 5<br>mm      | 22.25 in;<br>565 mm        | -                                         | 52 lb·ft²;<br>2.18<br>kg·m² | -                      | 0.26 in; 7<br>mm     | 8                    | -                      |
| <a href="#">12CB350<br/>10111</a>    | 16.00 in;<br>406 mm   | -                          | -                                         | -                           | 208 lb; 94<br>kg       | -                    | -                    | -                      |
| <a href="#">18CB500<br/>406908</a>   | 115 mm                | -                          | -                                         | -                           | 96 mm                  | -                    | 19 kg                | 6000<br>min-1          |
| <a href="#">40CB525<br/>411872</a>   | 74 kg                 | -                          | -                                         | -                           | -                      | 0.0175<br>kg·m²      | 4700<br>min-1        | -                      |
| <a href="#">12CB350<br/>0 407049</a> | 22CB500               | -                          | 21.87 in;<br>555 mm                       | -                           | -                      | -                    | -                    | 28.38 in;<br>721 mm    |
| <a href="#">14CB400<br/>0 411861</a> | -                     | 0.63 in; 16<br>mm          | 150 psi;<br>10.3 bar                      | -                           | -                      | 0.69 in; 18<br>mm    | 1-14                 | -                      |
| <a href="#">12CB350<br/>406902</a>   | 5.187 in;<br>131.7 mm | 411863                     | -                                         | 406908                      | 14.00 in;<br>356 mm    | -                    | 641 mm;<br>25.25 in  | -                      |
| <a href="#">28CB525<br/>406918</a>   | 2.3 in; 58<br>mm      | -                          | 4.45 in;<br>4.49 in;<br>113 mm;<br>114 mm | -                           | -                      | -                    | 1.00 in; 19<br>mm    | -                      |
| <a href="#">8CB250<br/>10109</a>     | -                     | 0.19 in                    | -                                         | 16.625 in                   | -                      | -                    | -                    | -                      |
| <a href="#">36CB525<br/>411871</a>   | 143 mm                | -                          | -                                         | -                           | 0.4 mm                 | 117 mm               | -                    | -                      |
| <a href="#">30CB525<br/>411869</a>   | -                     | -                          | Tapped<br>Holes                           | -                           | -                      | -                    | -                    | -                      |
| <a href="#">14CB400<br/>406904</a>   | -                     | -                          | -                                         | -                           | -                      | -                    | -                    | -                      |
| <a href="#">28CB525<br/>411868</a>   | -                     | 31800<br>lb·in; 3570<br>Nm | 0.63 in;<br>16.0 mm                       | 16.00 in;<br>406.4 mm       | -                      | 4.38 in;<br>111.3 mm | -                    | -                      |
| <a href="#">40CB525<br/>407065</a>   | -                     | -                          | 142 mm                                    | -                           | -                      | -                    | -                    | 30 °                   |
| <a href="#">26CB525<br/>408289</a>   | Tapped<br>Holes       | 4.00 in;<br>102 mm         | -                                         | 358 lb;<br>162 kg           | -                      | -                    | -                    | -                      |
| <a href="#">10CB300<br/>1011</a>     | -                     | -                          | 15.3 in;<br>389 mm                        | -                           | 0.50 in;<br>3/8-18 in; | 0.36 in; 9<br>mm     | 0.875 in;<br>22.2 mm | 1.7 in; 43<br>mm       |

|                                           |                                                         |                   |                     |                            |                                      |                        |                     |                    |
|-------------------------------------------|---------------------------------------------------------|-------------------|---------------------|----------------------------|--------------------------------------|------------------------|---------------------|--------------------|
|                                           |                                                         |                   |                     |                            | 13 mm;<br>3/8-18<br>mm               |                        |                     |                    |
| <a href="#">18CB500<br/>408285</a>        | -                                                       | -                 | 146506B<br>R        | 11.94 in;<br>303 mm        | -                                    | 18.8 in;<br>478 mm     | -                   | -                  |
| <a href="#">18CB500<br/>411863</a>        | 1424 lb;<br>646 kg                                      | -                 | -                   | 1.25 in; 32<br>mm          | -                                    | -                      | -                   | -                  |
| <a href="#">30CB525<br/>142439D<br/>A</a> | -                                                       | -                 | -                   | -                          | -                                    | -                      | -                   | -                  |
| <a href="#">22CB500<br/>142266K<br/>M</a> | -                                                       | 0.81 in; 21<br>mm | 16.19 in;<br>411 mm | 70400<br>lb·in; 7960<br>Nm | -                                    | -                      | -                   | -                  |
| <a href="#">6CB200<br/>142095JG</a>       | 0.00 in;<br>0.0 mm                                      | -                 | 3.75 in;<br>95.3 mm | -                          | 1800 rpm                             | -                      | -                   | 5/8" -<br>11NF     |
| <a href="#">12CB350<br/>142731D<br/>A</a> | Spring<br>Applied, E<br>lectro-<br>Hydraulic<br>Release | -                 | -                   | -                          | 750 Nm                               | 13 mm                  | 582 mm              | -                  |
| <a href="#">12CB350<br/>142098JG</a>      | -                                                       | -                 | -                   | -                          | -                                    | 0.75 in; 19<br>mm      | -                   | 6.50 in;<br>165 mm |
| <a href="#">45CB525<br/>142443D<br/>A</a> | -                                                       | Tapped<br>Holes   | -                   | -                          | -                                    | -                      | -                   | 0.75 in; 19<br>mm  |
| <a href="#">8CB250<br/>142096JG</a>       | -                                                       | -                 | -                   | 411861                     | -                                    | -                      | -                   | -                  |
| <a href="#">24CB500<br/>142436D<br/>A</a> | 90811<br>lb·in;<br>10080 Nm                             | 358 lb;<br>162 kg | Air<br>Applied      | -                          | Wichita<br>Clutch                    | 4.00 in;<br>101.6 mm   | -                   | -                  |
| <a href="#">32CB525<br/>142271K<br/>M</a> | -                                                       | -                 | -                   | -                          | Spring<br>Applied,<br>Air<br>Release | 18.250 in;<br>463.5 mm | 11.00 in;<br>279 mm | 8                  |
| <a href="#">22CB500<br/>142435D<br/>A</a> | -                                                       | -                 | -                   | -                          | -                                    | -                      | -                   | 6.50 in;<br>165 mm |
| <a href="#">28CB525<br/>142438D<br/>A</a> | -                                                       | -                 | -                   | -                          | -                                    | 15.00 in               | 765 rpm             | -                  |
| <a href="#">40CB525<br/>142442D<br/>A</a> | -                                                       | -                 | -                   | -                          | 461.00<br>lb·ft²;<br>19.36<br>kg·m²  | -                      | 45CB525             | -                  |
| <a href="#">16CB500<br/>142211K</a>       | -                                                       | 110 V             | -                   | 155 mm                     | -                                    | Pintsch<br>Bubenzer    | -                   | 0.4 mm             |

|                                                                         |                              |                       |                     |                        |                      |                     |                                                      |                                                  |
|-------------------------------------------------------------------------|------------------------------|-----------------------|---------------------|------------------------|----------------------|---------------------|------------------------------------------------------|--------------------------------------------------|
| <a href="#">M</a>                                                       |                              |                       |                     |                        |                      |                     |                                                      |                                                  |
| <a href="#">20CB500</a><br><a href="#">142434D</a><br><a href="#">A</a> | -                            | -                     | -                   | -                      | -                    | -                   | -                                                    | -                                                |
| <a href="#">10CB300</a><br><a href="#">406903</a>                       | Air<br>Applied               | -                     | -                   | -                      | 1.750 thru<br>2.500  | -                   | 0.531 in;<br>13.5 mm                                 | -                                                |
| <a href="#">18CB500</a><br><a href="#">408286</a>                       | -                            | -                     | -                   | 16.750 in;<br>425.5 mm | -                    | -                   | -                                                    | -                                                |
| <a href="#">30CB525</a><br><a href="#">408344</a>                       | -                            | 6.00 in;<br>152 mm    | -                   | 254 mm;<br>10.00 in    | 8.00 in;<br>203 mm   | -                   | 1294 lb;<br>587 kg                                   | 11.00 in;<br>279 mm                              |
| <a href="#">8CB250</a><br><a href="#">407046</a>                        | -                            | -                     | 2.50 in; 64<br>mm   | 411862                 | -                    | -                   | 53 lb·ft <sup>2</sup> ;<br>2.23<br>kg·m <sup>2</sup> | 24.00 in;<br>610 mm                              |
| <a href="#">6CB200</a><br><a href="#">408415</a>                        | 2.38 in; 60<br>mm            | 1.52 in; 39<br>mm     | 3300 lb;<br>1497 kg | 16.50 in;<br>419 mm    | -                    | -                   | -                                                    | 4.88 in;<br>124 mm                               |
| <a href="#">24CB500</a><br><a href="#">407058</a>                       | -                            | -                     | 164 lb; 74<br>kg    | 406916                 | 5.90 in;<br>150 mm   | 34.63 in;<br>880 mm | -                                                    | C2                                               |
| <a href="#">32CB525</a><br><a href="#">406923</a>                       | 0.28 in;<br>0.38 in          | -                     | 1.750 thru<br>2.500 | -                      | -                    | -                   | 2.563 thru<br>3.125                                  | 12.78 in;<br>325 mm                              |
| <a href="#">26CB525</a><br><a href="#">406917</a>                       | Air<br>Applied               | -                     | -                   | -                      | -                    | -                   | -                                                    | -                                                |
| <a href="#">6CB200</a><br><a href="#">407044</a>                        | 211000<br>lb·in;<br>23800 Nm | 819 mm;<br>32.25 in   | 4.88 in;<br>124 mm  | 7.60 in;<br>193 mm     | -                    | 10.10 in;<br>257 mm | -                                                    | 344 lb;<br>156 kg                                |
| <a href="#">8CB250</a><br><a href="#">406901</a>                        | -                            | -                     | -                   | -                      | 0.63 in; 16<br>mm    | -                   | -                                                    | -                                                |
| <a href="#">20CB500</a><br><a href="#">406911</a>                       | 13.41 in;<br>341 mm          | -                     | 1.750 thru<br>2.500 | -                      | -                    | -                   | -                                                    | -                                                |
| <a href="#">20CB500</a><br><a href="#">407056</a>                       | 406904                       | 408376                | 35 lb; 16<br>kg     | -                      | -                    | 4.34 in;<br>110 mm  | 83 lb; 38<br>kg                                      | 127 mm;<br>5.00 in                               |
| <a href="#">36CB525</a><br><a href="#">406925</a>                       | -                            | -                     | -                   | -                      | -                    | -                   | -                                                    | -                                                |
| <a href="#">16CB500</a><br><a href="#">407054</a>                       | -                            | -                     | -                   | -                      | -                    | -                   | -                                                    | -                                                |
| <a href="#">40CB525</a><br><a href="#">407066</a>                       | 26.81 in;<br>681 mm          | 51.75 in;<br>1314 mm  | -                   | -                      | 65.00 in;<br>1651 mm | 4                   | -                                                    | -                                                |
| <a href="#">32CB525</a><br><a href="#">407062</a>                       | 128 mm                       | -                     | 171 mm              | -                      | 46 mm                | 2.3 mm              | -                                                    | -                                                |
| <a href="#">16CB500</a><br><a href="#">406907</a>                       | -                            | -                     | -                   | -                      | -                    | -                   | -                                                    | 0.50 in;<br>3/8-18 in;<br>13 mm;<br>3/8-18<br>mm |
| <a href="#">12CB350</a><br><a href="#">406903</a>                       | 1100 rpm;<br>1700 rpm        | 1.500 in;<br>2.250 in | 3.50 in; 89<br>mm   | -                      | -                    | -                   | 10CB300                                              | 8.56 in;<br>217 mm                               |
| <a href="#">26CB525</a>                                                 | -                            | -                     | -                   | -                      | -                    | 1.0 mm              | 106 mm                                               | -                                                |

|                                                     |                                                                        |                             |                             |                     |                       |                                     |                                                        |                                                  |
|-----------------------------------------------------|------------------------------------------------------------------------|-----------------------------|-----------------------------|---------------------|-----------------------|-------------------------------------|--------------------------------------------------------|--------------------------------------------------|
| <a href="#">408342</a>                              |                                                                        |                             |                             |                     |                       |                                     |                                                        |                                                  |
| <a href="#">24CB500</a><br><a href="#">406915</a>   | -                                                                      | 0.0048<br>kg·m <sup>2</sup> | A300;<br>A350               | 30 °                | -                     | 38 mm; 42<br>mm; 48<br>mm; 55<br>mm | 6000<br>min-1                                          | 1.2 mm                                           |
| <a href="#">14CB400</a><br><a href="#">406905</a>   | -                                                                      | -                           | -                           | -                   | 4.752 in;<br>120.7 mm | 32 lb·ft <sup>2</sup> ;<br>1.34     | 2.88 in; 73<br>mm                                      | -                                                |
| <a href="#">28CB525</a><br><a href="#">406919</a>   | 45.51 in;<br>1156 mm                                                   | -                           | 26.76 in;<br>680 mm         | 7-336AM-<br>W-1300  | 16.5 in;<br>419 mm    | 2550 hp;<br>1902 kW                 | -                                                      | -                                                |
| <a href="#">30CB525</a><br><a href="#">406921</a>   | -                                                                      | -                           | -                           | 20                  | 15900<br>lb·in        | Wichita<br>Clutch                   | -                                                      | -                                                |
| <a href="#">28CB525</a><br><a href="#">40706</a>    | -                                                                      | -                           | -                           | 1.7 in; 43<br>mm    | -                     | -                                   | 1.250 thru<br>2.000                                    | -                                                |
| <a href="#">45CB525</a><br><a href="#">406929</a>   | -                                                                      | -                           | -                           | 1.44 in; 37<br>mm   | -                     | -                                   | 5.937 in;<br>150.8 mm                                  | -                                                |
| <a href="#">36CB525</a><br><a href="#">407064</a>   | -                                                                      | -                           | -                           | 819 mm;<br>32.25 in | 344 lb;<br>156 kg     | 3/4 RH                              | 411872                                                 | -                                                |
| <a href="#">22CB500</a><br><a href="#">406913</a>   | 2040 lb·in;<br>231 Nm                                                  | 1.38 in; 35<br>mm           | -                           | -                   | -                     | -                                   | -                                                      | -                                                |
| <a href="#">18CB500</a><br><a href="#">406909</a>   | 0.54 in; 14<br>mm                                                      | 8CB250                      | -                           | -                   | -                     | -                                   | -                                                      | 2.50 in; 64<br>mm                                |
| <a href="#">14CB400</a><br><a href="#">0 407051</a> | 8; 0.781<br>in; 20 mm                                                  | -                           | 18 in; 457<br>mm            | -                   | -                     | -                                   | -                                                      | 31 lb·ft <sup>2</sup> ;<br>1.3 kg·m <sup>2</sup> |
| <a href="#">8CB250</a><br><a href="#">4069</a>      | 141 mm                                                                 | -                           | 0.0037<br>kg·m <sup>2</sup> | -                   | -                     | -                                   | 128 W                                                  | -                                                |
| <a href="#">24CB500</a><br><a href="#">411866</a>   | -                                                                      | -                           | -                           | -                   | -                     | -                                   | -                                                      | -                                                |
| <a href="#">16CB500</a><br><a href="#">411862</a>   | 8.406 in;<br>213.5 mm                                                  | 287 lb;<br>130 kg           | 1/2-14 in                   | 319 lb;<br>145 kg   | 178 lb; 81<br>kg      | -                                   | 710 lb·ft <sup>2</sup> ;<br>29.82<br>kg·m <sup>2</sup> | 819 mm;<br>32.25 in                              |
| <a href="#">24CB500</a><br><a href="#">406914</a>   | 1.59 E-06<br>bar/rpm <sup>2</sup> ;<br>23 E-06<br>psi/rpm <sup>2</sup> | -                           | 0.26 in; 7<br>mm            | -                   | -                     | -                                   | -                                                      | -                                                |
| <a href="#">36CB525</a><br><a href="#">407063</a>   | 686000 lb-<br>in @ 80<br>psi; 77508<br>Nm @ 5.5<br>bar                 | Air<br>Applied              | 14.42 in;<br>366 mm         | -                   | 3694 lb;<br>1676 kg   | 16                                  | -                                                      | -                                                |
| <a href="#">16CB500</a><br><a href="#">406906</a>   | 9.63 in;<br>245 mm                                                     | -                           | -                           | 2.4 in; 31<br>mm    | -                     | -                                   | -                                                      | -                                                |
| <a href="#">16CB500</a><br><a href="#">407053</a>   | -                                                                      | 406912                      | -                           | -                   | 1.44 in; 37<br>mm     | 8.30 in;<br>211 mm                  | -                                                      | Eaton-<br>Airflex                                |
| <a href="#">18CB500</a><br><a href="#">403257</a>   | -                                                                      | -                           | -                           | -                   | -                     | -                                   | -                                                      | -                                                |
| <a href="#">10CB300</a>                             | 150 lb·ft <sup>2</sup> ;                                               | 75000                       | -                           | 5.60 in;            | -                     | 173 lb; 79                          | -                                                      | -                                                |

|                                                   |                       |                                                                 |                                                    |                                                                  |                                     |                      |                                                                                                             |                                                     |
|---------------------------------------------------|-----------------------|-----------------------------------------------------------------|----------------------------------------------------|------------------------------------------------------------------|-------------------------------------|----------------------|-------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| <a href="#">407047</a>                            | 6.3 kg·m <sup>2</sup> | lb·in; 8480 Nm                                                  |                                                    | 142 mm                                                           |                                     | kg                   |                                                                                                             |                                                     |
| <a href="#">20CB500</a><br><a href="#">40691</a>  | 5.906 in;<br>150.0 mm | 6.60 in;<br>168 mm                                              | -                                                  | 730 mm;<br>28.75 in                                              | -                                   | -                    | 268 lb·ft <sup>2</sup> ;<br>11.26 kg·m <sup>2</sup>                                                         | 252 lb·ft <sup>2</sup> ;<br>10.58 kg·m <sup>2</sup> |
| <a href="#">6CB200</a><br><a href="#">408414</a>  | -                     | -                                                               | 178 lb·ft <sup>2</sup> ;<br>7.48 kg·m <sup>2</sup> | -                                                                | -                                   | -                    | -                                                                                                           | -                                                   |
| <a href="#">14CB400</a><br><a href="#">9617</a>   | 185 mm                | -                                                               | -                                                  | -                                                                | Spring Applied,<br>Electric Release | -                    | Ed 50/6 for 8500 N Contract Force; Ed 80/6 for 12500 N Contract Force; Ed 80/7bb for 16000 N Contract Force | 120 mm                                              |
| <a href="#">26CB525</a><br><a href="#">411867</a> | 0.69 in; 17 mm        | -                                                               | 17.625 in;<br>447.7 mm                             | 0.83 E-06 bar/rpm <sup>2</sup> ;<br>12 E-06 psi/rpm <sup>2</sup> | -                                   | -                    | 8.75 in;<br>222 mm                                                                                          | -                                                   |
| <a href="#">28CB525</a><br><a href="#">407059</a> | 3.25 in; 83 mm        | -                                                               | -                                                  | 1 RH                                                             | -                                   | -                    | -                                                                                                           | -                                                   |
| <a href="#">22CB500</a><br><a href="#">411865</a> | -                     | Over five million cycles at 75 psi (5.2 bar) and 80 °F (27 °C). | -                                                  | -                                                                | Zinc alloy                          | 150 psi;<br>10.3 bar | 0.750 in                                                                                                    | -                                                   |
| <a href="#">6CB2</a>                              | -                     | -                                                               | -                                                  | -                                                                | -                                   | -                    | -                                                                                                           | -                                                   |
| <a href="#">6CB200</a><br><a href="#">10108</a>   | -                     | -                                                               | -                                                  | 7.06 in;<br>179 mm                                               | -                                   | -                    | 26 in; 660 mm                                                                                               | 19.500 in;<br>495.3 mm                              |
| <a href="#">26CB525</a><br><a href="#">406916</a> | -                     | -                                                               | -                                                  | -                                                                | -                                   | -                    | 0.75 in; 19 mm                                                                                              | -                                                   |
| <a href="#">40CB525</a><br><a href="#">406926</a> | 45CB525               | -                                                               | -                                                  | -                                                                | -                                   | 6.00 in;<br>152 mm   | -                                                                                                           | -                                                   |
| <a href="#">20CB500</a><br><a href="#">407055</a> | 303 mm;<br>350 mm     | -                                                               | 0.0068 kg·m <sup>2</sup>                           | -                                                                | 0.3 mm                              | 30 °                 | Spring Applied,<br>Electric Release                                                                         | -                                                   |
| <a href="#">20CB500</a><br><a href="#">411864</a> | 932 lb;<br>422 kg     | 1.44 in; 37 mm                                                  | 198 lb; 90 kg                                      | -                                                                | -                                   | 4.50 in;<br>114 mm   | -                                                                                                           | 165 mm;<br>6.50 in                                  |

|                                     |                       |                     |                    |                        |        |                                           |                     |                                           |
|-------------------------------------|-----------------------|---------------------|--------------------|------------------------|--------|-------------------------------------------|---------------------|-------------------------------------------|
| <a href="#">6CB200<br/>407043</a>   | -                     | -                   | 95 mm              | 4000<br>min-1          | -      | -                                         | -                   | Spring<br>Applied,<br>Electric<br>Release |
| <a href="#">24CB500<br/>50234</a>   | 1000 lb·in;<br>113 Nm | -                   | 2.00 in; 51<br>mm  | -                      | -      | 6.69 in;<br>170 mm                        | -                   | -                                         |
| <a href="#">32CB525<br/>41187</a>   | -                     | -                   | 8.91 A             | -                      | -      | -                                         | -                   | 310 mm                                    |
| <a href="#">10CB300<br/>406902</a>  | -                     | -                   | -                  | 446 mm                 | 330 mm | Spring<br>Applied,<br>Electric<br>Release | Pintsch<br>Bubenzer | 3.13 A                                    |
| <a href="#">24CB500<br/>407057</a>  | Wichita<br>Clutch     | 7-027-100<br>-100-0 | -                  | -                      | -      | 137509<br>lb·in;<br>15260 Nm              | -                   | -                                         |
| <a href="#">8CB25</a>               | -                     | -                   | -                  | -                      | -      | -                                         | -                   | 5.25 in;<br>133 mm                        |
| <a href="#">32CB525<br/>407061</a>  | -                     | -                   | -                  | 19.750 in;<br>501.7 mm | -      | -                                         | -                   | -                                         |
| <a href="#">32CB525<br/>406922</a>  | -                     | -                   | 165 mm;<br>6.50 in | 95 lb; 43<br>kg        | -      | C2                                        | 8.30 in;<br>211 mm  | -                                         |
| <a href="#">8CB250<br/>407045</a>   | -                     | -                   | -                  | -                      | -      | 171 mm                                    | -                   | 232 mm                                    |
| <a href="#">22CB500<br/>408287</a>  | -                     | -                   | -                  | -                      | 110 V  | -                                         | 6000<br>min-1       | 0.0037<br>kg·m²                           |
| <a href="#">10CB3</a>               | 28.00 in;<br>711 mm   | -                   | Eaton-<br>Airflex  | 3.81 in; 97<br>mm      | -      | -                                         | 406910              | -                                         |
| <a href="#">45CB525<br/>406928</a>  | Air<br>Applied        | Eaton-<br>Airflex   | 6.60 in;<br>168 mm | 40.63 in;<br>1032 mm   | -      | -                                         | 392 lb;<br>178 kg   | -                                         |
| <a href="#">12CB350<br/>0 41186</a> | -                     | -                   | 0.02               | 60                     | 2.2    | 17/32 in;<br>13.5 mm                      | -                   | 7.69 in;<br>195.3 mm                      |

Square D vs Siemens Electrical Panel: Which To Choose? Jul 19, 2021 — The QO load centers are compatible with 3/4" circuit breakers with Visi-Trip technology, and shielded tin-plated copper bus bars, which is an

ul-classified-replacement-circuit-breakers - Eaton We test each Classified breaker extensively in numerous GE, Siemens, Murray, Thomas & Betts, Square D, and Crouse-Hinds panels. The tests are conducted with Missing: Rubflex ?Friction Square D Homeline and QO breakers for your breaker box Square D QO breakers are compatible with QO breaker boxes and CSEDs. Each ANSI-certified and UL-listed. Homeline circuit breakers are built with the same Square