

Is Rubflex Friction VC same as Cutler-Hammer?

Our company offers different Is Rubflex Friction VC same as Cutler-Hammer? at Wholesale Price? Here, you can get high quality and high efficient Is Rubflex Friction VC same as Cutler-Hammer?

Are Cutler-Hammer products the same as Eaton products? Cutler-Hammer and the Eaton family of products are the same and compatible. Part numbers have not changed, just the Eaton name has been placed on the

New Cutler Hammer circuit breakers BAB, GHB, EHD, FD, KD Stock orders placed by 3PM EST ship same day. US Breaker, Inc. provides cross references to our US Breaker brand high quality UL Square D vs. Cutler hammer - HouzzIt is not so black and white. Cutler Hammer CH series is about the same as SqD QO series, both are considered "high end" for residential installations. Cutler

Industrial Clutch and Brakes								
	G MM	H6 MM	H7 MM	D2 MM	G1 MM	H2 MM	D24 MM	D25 MM
28CB52510415	-	-	-	-	-	-	-	-
52VC1200 509709	1502 lb·ft²; 63.08 kg·m²	40.19 in; 1021 mm	47.25 in; 1200 mm	47.125 in; 1197 mm	-	40CB525	0.84 in; 21 mm	12.69 in; 322 mm
35CM500146207	17.50 in; 444.5 mm	3.50 in; 89 mm	-	-	-	-	2450 rpm	55250 lb·in; 6200 Nm
26CB525104427	-	-	3.75 in; 95 mm	-	-	-	-	-
32CB525142271	2.00 in; 50.8 mm	48 psi; 3.31 bar	14.68 in; 372.9 mm	23 psi; 1.59 bar	0.94 in; 23.9 mm	11.50 in; 292.1 mm	-	-
11.5VC500 104298	19.87 in; 505 mm	13.62 in; 346 mm	6 - 1.25 NPT	0.25 in; 6.4 mm	8.13 in; 207 mm	28.750 in; 730.25 mm	-	-
4CB200142840JB	-	-	-	-	1.75 in; 44 mm	0.155 in²; 1 cm²	-	-
40CM550146208	-	-	22.500 °	-	-	-	23.500 in; 596.9 mm	0.06 in; 2 mm
14VC500107595	-	-	-	-	-	-	-	-
48CM650512246	6.94 in; 176 mm	458 in²; 2954 cm²	121000 lb·in; 13700 Nm	36.50 in; 927 mm	-	0.50 in; 13 mm	-	30CB525
51VC1600 509649	4.06 in; 103 mm	-	-	6.250 in; 158.8 mm	Thru Holes	-	-	10 in; 254 mm

38VC120 0 104704	-	-	-	-	-	Eaton- Airflex	-	-
24VC650 105437	-	-	-	-	-	-	-	-
20VC600 10462	-	-	-	-	-	-	-	12CB350
20VC600 509698	13.63 in; 346 mm	-	0.81 in; 21 mm	0.500 in; 13 mm	-	-	-	-
22CB500 104147	2.00 in; 50.8 mm	6.00 in; 152 mm	Air Applied	-	12.25 in; 311.2 mm	-	6.00 in; 152.4 mm	1410 rpm
26CB525 142268	-	-	-	-	-	-	-	-
46VC120 0 142671	16.50 in; 419.1 mm	294 gpm; 1107 lpm	-	-	14.00 in; 355.6 mm	0.8 in; 2.0 cm; 500 in ³ ; 8.2 dm ³	-	-
24CB500 142436	-	24.375 in; 619.1 mm	-	-	-	-	5.00 in; 127 mm	-
42VC120 0 107608	-	-	-	-	-	-	-	3.500 in; 88.9 mm
20VC100 0 509698	-	1.00 in; 25 mm	-	-	-	-	-	-
38VC120 0 142739	-	-	-	-	-	-	-	1.00 in; 25 mm
32CB525 14244	-	-	-	-	-	-	-	-
30CB525 142270KT	6.94 in; 176 mm	11.250 °	-	-	-	-	0.50 in; 13 mm	-
22CB500 105505	1/2-14	6.00 in; 152 mm	3/8-16 in; 3/8-16 mm	21500 lb- in @ 80 psi; 2429 Nm @ 5.5 bar	-	-	0.27; 6.4	3/4-10
14VC500 105862	-	-	-	0.44 in; 11 mm	-	-	-	Eaton- Airflex
42VC650 502369	-	-	-	-	4.38 in; 111.3 mm	-	0.4 in; 1.0 cm; 10 in ³ ; 0.2 dm ³	2- 1/2 NPT
46VC120 0 104706	670 rpm	-	-	5.25 in; 133 mm	45.19 in; 1148 mm	-	-	0.750 in; 19 mm
60VC160 0 509711	19.500 in; 495.3 mm	-	-	-	26CB525	-	-	-
24VC850 509699	-	400 mm	-	2050 Nm	-	-	-	-
11.5VC50 0 107594	22 in; 559 mm	-	-	-	6.62 in; 168 mm	-	-	-

16VC100 0 10472	-	-	-	-	-	-	177 lb; 148 kg	-
38VC120 0 409474	3/8-18 in	-	0.531 in; 13.5 mm	-	1.5 in; 38 mm	-	-	17.62 in; 448 mm
28VC100 0 409537	-	-	16.50 in; 419.1 mm	17.38 in; 441.5 mm	5.63 in; 143 mm	-	-	Wichita Clutch
51VC160 0 409711	-	190 lb; 86 kg	-	-	-	2400 rpm	-	0.38 in; 10 mm
52VC120 0 409715	-	555 hp; 414 kW	-	-	-	-	-	23.25 in; 591 mm
24VC100 0 409794	0.25 in; 6.4 mm	-	29.50 in; 749.3 mm	-	800 rpm	-	52.00 in; 1320.8 mm	6-042-200 -309-0
42VC120 0 409947	B3	-	-	2.31 in; 59 mm	-	-	0.31 in; 8 mm	-
46VC120 0 40998	-	19.62 in; 498 mm	2.0 in; 51 mm	-	3/8-18 in	-	5.22 in; 133 mm	-
20VC100 0 410087	6.250 in; 158.8 mm	2.00 in; 51 mm	17.62 in; 448 mm	2.5 in; 64 mm	-	-	-	-
16VC100 0 409506	-	-	-	-	-	-	4CB200	7.25 in; 184 mm
32VC100 0 410824	-	-	-	-	-	Eaton- Airflex	-	1.750 thru 2.500
60VC160 0 411501	-	-	Air Applied	13300 lb·in	-	3/8-18 in	-	2.00 in; 51 mm
66VC160 0 413727	765 rpm	-	-	-	327000 lb·in; 37710 Nm	189 lb·ft²; 8.0 kg·m²	37.00 in; 939.8 mm	-
76VC160 0 515149	-	-	-	-	0.531 in; 13.5 mm	-	1.38 in; 2.25 in	-
76VC200 0 515382	-	-	-	-	-	-	-	3.3 in; 84 mm
14CB400 142087JA	-	2.50 in; 64 mm	-	-	-	4.50 in; 114 mm	408279	-
10CB300 142197JA	540 Nm	-	-	-	18 mm	-	118 mm	68 kg
4CB200 142840JA	6.250 in; 158.8 mm	-	1.44 in; 37 mm	-	-	-	-	-
12CB350 142098JA	Air Applied	-	-	-	1.91 in; 49 mm	-	-	8.22 in; 209 mm
6CB200 142095JA	-	3/8-18 in	-	-	-	-	2.00 in; 51 mm	-
8CB250 142096JA	-	3/8-18 in	-	-	6	14CB400	-	1/4-18 in
14CB400 142087JA	64 in	-	-	1.250 thru 2.000	6.88 in; 175 mm	-	-	-

16CB500142211KY	-	-	-	Air Applied	-	-	9.06 in; 230 mm	3/8-18 in
18CB500142264KY	-	-	-	-	-	10.75 in; 273 mm	-	-
20CB500142265KY	3.56 in; 90 mm	-	408376	-	-	6.70 in; 170 mm	-	-
22CB500142266KY	-	4111 lb; 1865 kg	-	60 psi; 4.14 bar	9.00 in; 229 mm	Air Applied	-	-
24CB500142267KY	-	Air Applied	-	2.563 thru 3.125	-	1.3 in; 33 mm	-	-
26CB525142268KY	620 mm	-	-	-	-	Pintsch Bubenzer	282 mm	30 °
26CB525142269KY	3.25 in; 83 mm	21000 lb·in; 2370 Nm	70 lb; 32 kg	1 lb·ft ² ; 0.04 kg·m ²	-	12.37 in; 314 mm	2	-
30CB525142270KY	1/8-27 in	-	-	-	-	-	1/8-27 in	-
32CB525142271KY	-	14.38 in; 365 mm	-	-	2.563 thru 3.125	-	-	4.38 in
36CB525142272KY	-	-	10 in; 7 in	2.563 thru 3.125	-	-	-	-
40CB525142273KY	-	-	-	-	-	-	-	-
45CB525142443KY	-	Air Applied	8.30 in; 211 mm	227 lb; 103 kg	-	-	-	-
12CB350142098JA	-	-	-	-	-	Eaton-Airflex	1.88 in; 48 mm	-
4CB200142840JD	-	10 in	-	-	-	-	15.22 in	-
14CB400142087JC	-	-	-	-	-	Eaton-Airflex	-	-
6CB200142095JC	-	-	-	1.75 in; 44 mm	-	-	-	-
12CB350142098JC	-	2.5 in; 64 mm	10 in	-	-	-	-	-
8CB250142096JC	-	83 lb·ft ² ; 3.5 kg·m ²	-	-	-	2.90 in; 74 mm	-	0.91 in; 23 mm
10CB300142197JC	262 lb; 119 kg	-	-	9.406 in; 238.9 mm	-	Eaton-Airflex	-	2691 lb; 1219 kg
16CB500142211KP	14	-	92 lb·ft ² ; 3.87 kg·m ²	-	-	Air Applied	-	21/32 in; 16.7 mm
18CB500142264KP	-	406920	-	-	-	4.50 in; 114 mm	-	69 lb·ft ² ; 2.9 kg·m ²
20CB500142265KP	-	-	-	-	-	15 lb; 6.8 kg	2.50 in; 64 mm	-

22CB500 142266KP	-	1.28 in; 33 mm	-	-	150 psi; 10.3 bar	-	Eaton-Airflex	376 ft ³ /min; 17.2 m ³ /min
24CB500 142267KP	-	-	-	-	-	-	6.250 in; 209.6 mm	Eaton-Airflex
26CB525 142268KP	49.25 in; 1251 mm	211000 lb·in; 23800 Nm	Air Applied	4.88 in; 124 mm	Eaton-Airflex	-	-	774 lb·ft ² ; 32.51 kg·m ²
26CB525 142269KP	-	-	-	-	-	-	-	-
30CB525 142270KP	8	1.1 in; 28 mm	6.69 in; 170 mm	-	-	-	1/4-18 in	Air Applied
32CB525 142271KP	-	-	137 mm	Spring Applied, Electric Release	-	Pintsch Bubenzer	-	-
36CB525 142272KP	-	-	-	-	-	-	-	-
40CB525 142273KP	11.50 in; 292 mm	1.75 in; 44 mm	935 lb; 424 kg	-	7.000 in; 178 mm	-	Eaton-Airflex	-
45CB525 142443KP	-	-	-	-	2.69 in	-	-	-
12CB350 142098JG	-	24CB500	1.00 in; 25 mm	-	-	-	18.000 in; 457.2 mm	-
14CB400 142087JG	-	2691 lb; 1219 kg	1887 lb·ft ² ; 79.25 kg·m ²	-	411873	262 lb; 119 kg	11.00 in; 279 mm	254 mm; 10.00 in
4CB200 14284	2.88 in; 4.38 in	-	-	-	-	Air Applied	-	-
32CB525 14244	-	-	-	-	10.75 in; 273 mm	-	-	-
66VC160 0 Consult Factory	-	10CB300	-	-	-	-	4.44 in; 113 mm	-
14CB400 142087	-	4290 lb·in	0.94 in; 24 mm	-	-	5.250 in; 133.4 mm	-	-
36CB525 142441	-	-	-	1000 rpm; 1350 rpm	-	-	2.88 in; 73 mm	-
14VC100 0 508545	-	-	-	-	-	-	-	9.64 in; 227 mm
26CB525 142268	-	8.00 in; 203 mm	-	-	-	-	-	-
42VC650 142647	407098	-	8.50 in; 216 mm	8.406 in; 213.5 mm	-	-	7.10 in; 180 mm	-

26CB525104129	-	-	30 °	-	-	-	110 V	0.4 mm
24CB500104148	-	80900 lb·in; 9140 Nm	-	-	-	-	-	-
20VC1000104681	-	411866	4.50 in; 114 mm	408280	-	257 lb; 117 kg	-	150 lb·ft²; 6.3 kg·m²
76VC16	19700 lb·in	-	-	-	-	2.00 in; 51 mm	-	-
40CB525142442	-	4100 Nm	-	630 mm	-	-	-	-
20VC600104299	-	8.406 in; 213.5 mm	4.00 in; 102 mm	407098	-	-	-	2.75 in; 70 mm
45CB525142443	-	-	-	-	-	-	5.3 lb·ft²; 0.22 kg·m²	Eaton-Airflex
DW76HEVC16	-	3/4 RH	-	4.31 in; 109 mm	146506B R	-	1.750 in; 44.5 mm	0.62 in; 16 mm
20VC600107597	-	-	14.88 in; 378 mm	-	-	-	-	-
14CB400142604	-	-	-	-	-	2.7 in; 61 mm	-	-
24VC650107598	-	2.563 thru 3.125	9.28 in; 136 mm	10 in; 7 in	-	87 in; 109 in	-	-
22CB500142435	-	406918	Eaton-Airflex	-	411868	-	1.44 in; 37 mm	337 lb; 153 kg
38VC1200107607	-	-	26.34 in; 669 mm	2285 lb·ft²; 9641 kg·m²	4975 lb; 2.261 kg	-	-	-

China Rubflex 66VC1600 Std Friction Shoe Kit Factory - Cheap Rubflex 66VC1600 Std Friction Shoe Kit. WE are the manufactuer of clutch brake in China. we supply VC clutch size from 14vc1000 to 76vc2000.

Are Eaton, Westinghouse, Square D, and Cutler Hammer Aug 8, 2018 — Most old and obsolete circuit breakers aren't compatible, but Eaton and Westinghouse are part of the same company.